

iQ700, Built-in compact oven with steam function, Stainless steel CS656GBS7B

























Included accessories

 $1 \times \text{grid}$, $1 \times \text{universal pan}$, $1 \times \text{steam}$ container, punched, size S, $1 \times \text{steam}$ container, punched, size XL, $1 \times \text{steam}$ container, unpunched, size S

Optional accessories

HZ915003 Glass roasting dish, 5,4 L H76FCC0 Cookbook HZ66X650 Cover Strip HZ66X600 Decor list HZ664000 Baking and roasting grid (steam) HZ638D18 1 telescopic rail, full ext, 45cm HZ636000 Glass pan Baking tray, anthracite enamelled HZ631070 HZ625071 Grill tray, anthracite enamelled HZ531010 Baking tray, non-stick ceramic coated HZ327000 Baking stone

Shorten your cooking time thanks to fast preheat and coolStart. And remote your oven from anywhere with Home Connect.

- ✓ fast preheat: reach the required baking temperature sooner; coolStart: no need to preheat the oven for deep frozen food.
- ✓ The full steam function: making it simple to cook healthy and delicious meals
- ✓ Home Connect: Allows access and control your oven, no matter where you are - with the easy-to-use Home Connect App
- \checkmark 4D hotAir: flexible choice of shelf.
- ✓ softMove: gentle opening and closing of the oven door.
- ✓ Remote Diagnostics: Let our professionals analyse appliance problems via remote access.

Feature

Technical Data

Color / Material Front : Stainless steel

Construction type : Built-in Door opening : Drop down

Required niche size for installation (HxWxD): 450-455 x 560-568 x

550

Dimensions of the product (mm): 455 x 594 x 548

Dimensions of the packed product (HxWxD) (mm) : 530 x 660 x 690

Control Panel Material: Stainless steel

Door Material : Glass Net weight (kg) : 34.040 Approval certificates : CE, VDE

Length of electrical supply cord (cm): 150

EAN code: 4242003839294

Current (A): 16
Voltage (V): 220-240
Frequency (Hz): 50; 60
Plug type: no plug
Approval certificates: CE, VDE

Number of cavities (2010/30/EC): 1 Usable volume (of cavity) - NEW (2010/30/EC): 47

Energy efficiency class (2010/30/EC): A+

Energy consumption per cycle conventional (2010/30/EC) : 0.73 Energy consumption per cycle forced air convection (2010/30/EC) :

0.61

Energy efficiency index (2010/30/EC): 81.3





iQ700, Built-in compact oven with steam function, Stainless steel CS656GBS7B

Features

Design

- 3.7" TFT touchDisplay
- Drop down oven door, softClose, softOpen
- Enamel anthracite
- Stainless steel control dial
- We recommend you to choose complementary products within IQ700, in order to assure an optimal design combination of your Built-In appliances.
- Control panel lock Automatic safety switch off Residual heat indicator Start button Door contact switch
- Digital temperature display with proposal Actual temperature display Heating-up indicator Sabbath setting
- WLAN Home connect enabled
- cookControl Plus
- Electronic oven clock timer
- LED light, Light on/off when door opened/closed
- Tank empty indicator
- Integral cooling fan
- 3 shelf positions

Cleaning

- EcoClean Direct : ceiling, back panel, side liners
- ecoClean programme
- Full glass inner door

Programmes/functions

- Compact steam oven with 13 main functions heating methods:
 4D hot air, hotairGentle, conventional top & bottom heating,
 Conventional heat Gentle, hot air grilling, full width grill, half width grill, Pizza setting, coolStart, bottom heat, low temperature cooking, keep warm, plate warming
- Additional heating methods with steam: steam, reheating, Dough proving, defrost
- Additional functions: Descaling programme Drying function autom. boiling point detection
- Fast preheat

Accessories

• 1 x steam container, punched, size S, 1 x steam container, punched, size XL, 1 x steam container, unpunched, size S, 1 x grid, 1 x universal pan

Performance/technical information

- Energy efficiency rating (acc. EU Nr. 65/2014): A+ Energy consumption per cycle in conventional mode: 0.73 kWh Energy consumption per cycle in fan-forced convection mode: 0.61 kWh Number of cavities: Main cavity Heat source: electrical Cavity volume: 47 litre capacity
- \bullet Temperature range 30 °C 250 °C
- Location of water tank: Outside cavity
- 1 | Water tank capacity:
- Power cord length 150 cm Cable length
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 455 mm x 594 mm x 548 mm
- Please refer to the dimensions provided in the installation manual