

iQ700, Canopy cooker hood, 70 cm, clear glass black printed LB79585MGB



A++



The powerful canopy cooker hood is concealed in a unit above the hob.

- ✓ The quiet high-performance motor: ensures efficient odour and steam removal.
- ✓ LED lights: For optimal visibility and ambience when cooking.
- ✓ For peak performance - Intensive setting with automatic revert

Features

Technical Data

Typology : Traditional
 Approval certificates : CE, VDE
 Length of electrical supply cord (cm) : 150
 Required niche size for installation (HxWxD) : 418mm x 676.0mm x 264mm
 Minimum distance above an electric hob : 500
 Minimum distance above a gas hob : 650
 Net weight (kg) : 9.517
 Type of control : Electronic
 Maximum output air extraction (m³/h) : 575
 Boost position output recirculating (m³/h) : 380.0
 Boost position air extraction (m³/h) : 775
 Number of lights (Stck) : 2
 Noise level (dB(A) re 1 pW) : 64
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable aluminium
 EAN code : 4242003845530
 Connection rating (W) : 172
 Current (A) : 3
 Voltage (V) : 220-240
 Frequency (Hz) : 50
 Plug type : GB plug
 Installation type : Built-in

Optional accessories

LZ75956	Remote control
LZ55750	Standard recirculation kit
LZ55651	Standard odor filter (replacement)
LZ11XC16	Clean Air Plus recirc. kit external
LZ11XB16	Clean Air Plus odor filter (replacement)
LZ11TD11	Long Life recirculation kit external
LZ10TP00	Long Life odor filter (replacement)



4 242003 845530

iQ700, Canopy cooker hood, 70 cm, clear glass black printed LB79585MGB

Features

Key performance features:

- Energy Efficiency Class: A++ (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm: max. Normal use 575 m³/h Intensive 775 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 64 dB dB*

Features

- Soft touch button control for extractor speeds and light
- 3 x power levels plus intensive setting
- Automatic intensive revert (6mins)
- 2 x 1W LED lights
- softLight with dimmer function
- Interval operation
- iQDrive motor - efficient BLDC technology
- Automatic after running (30 minutes)
- 2 x metal grease filter cassettes
- Saturation indicator for grease filter

Design

- Canopy hood
- For installation in a kitchen cabinet
- Glass filter cover, Steel filter cover
- Rim ventilation
- Black glass canopy
- Electronic control

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Max. extraction rate: 775 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air: Max. normal use: 64 dB(A) re 1 pW Intensive: 70 dB(A) re 1 pW
- Extraction rate in recirculation mode: Max. normal use: 310 m³/h Intensive: 380 m³/h
- Noise levels in recirculation mode: Max. normal use: 71 dB(A) re 1 pW Intensive: 75 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches: Extraction rate in recirculation mode: Max. normal use: 533 m³/h Intensive: 722 m³/h Noise level in recirculation mode: Max. normal use: 71 dB(A) re 1 pW Intensive: 77 dB(A) re 1 pW
- Power rating: 172 W
- Light Intensity: 244 lux
- Colour Temperature: 4000 K
- Electrical cable length 1.5 m
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*
- Average Energy Consumption: 30.3 kWh/year*
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 418-418 x 700 x 300 mm
- built-in dimensions (HxWxD): 418 x 676 x 264 mm

Optional accessories

- Recirculating kit LZ10ITP00

* In accordance with the EU-Regulation No 65/2014