


iQ300, Island cooker hood, 90 cm, clear glass LF97GBM50B

 **BUY NOW**



B



The island hood features an efficient extraction rate in the distinctive Siemens design.

- ✓ LED lights: For optimal visibility and ambience when cooking.
- ✓ Calms the cooking process -#Extremely quiet
- ✓ touchControl: quickly and easily manage the power levels and the LED light
- ✓ For peak performance - Intensive setting with automatic revert

Features

Technical Data

Typology : Chimney
 Approval certificates : CE, VDE
 Length of electrical supply cord (cm) : 130
 Height of the chimney (mm) : 698-878/698-998
 Height of product, without chimney (mm) : 46
 Net weight (kg) : 30.085
 Type of control : Electronic
 Maximum output air extraction (m3/h) : 429
 Boost position output recirculating (m3/h) : 384.0
 Boost position air extraction (m³/h) : 732
 Number of lights (Stck) : 4
 Noise level (dB(A) re 1 pW) : 60
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable aluminium
 EAN code : 4242003832110
 Connection rating (W) : 256
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : GB plug
 Installation type : Island



Optional accessories

LZ53650	Standard recirculation kit
LZ53251	Standard odor filter (replacement)
LZ31XXB16	Clean Air Plus odor filter (replacement)
LZ21CXC56	Clean Air Plus recirc. kit external
LZ12520	Extension for mounting kit 1000 mm
LZ12500	Extension for mounting kit 500 mm
LZ12400	Adapter for roof inclination front/back
LZ12375	Chimney extension 1600 mm
LZ12300	Adapter for roof inclination left/right
LZ12275	Chimney extension 1100 mm
LZ00XXP00	Long Life odor filter (replacement)

iQ300, Island cooker hood, 90 cm, clear glass LF97GBM50B

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm: max. Normal use 429 m³/h Intensive 732 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 60 dB dB*

Features

- touchControl with Electronic display
- 4 x 1.5W LED
- 3 x power levels plus intensive setting
- Automatic intensive revert (6mins)
- Steel filter cover
- 2 x metal grease filter cassettes

Design

- Stainless Steel
- Stainless steel hood with glass canopy
- For ceiling mounted installation
- Electronic control

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Max. extraction rate: 732 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air: Max. normal use: 60 dB(A) re 1 pW Intensive: 71 dB(A) re 1 pW
- Extraction rate in recirculation mode: Max. normal use: 315 m³/h Intensive: 384 m³/h
- Noise levels in recirculation mode: Max. normal use: 73 dB(A) re 1 pW Intensive: 77 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches: Extraction rate in recirculation mode: Max. normal use: 390 m³/h Intensive: 527 m³/h Noise level in recirculation mode: Max. normal use: 67 dB(A) re 1 pW Intensive: 73 dB(A) re 1 pW
- Power rating: 256 W
- Light Intensity: 502 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating, chimney (HxWxD): 744-1044 x 898 x 600 mm
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 71.3 kWh/year*

Optional accessories

- Recirculating kit LZ00XPP00

* In accordance with the EU-Regulation No 65/2014