Product specification Global Beau CF RCE



Name	Global Beau CF RCE						
Description	Free standing gas fire with frontal fire view, intended for installation in an						
•	existing fireplace. Remote control with electronic ignition.						
Purpose	Decorative fire						
Type of appliance	Free standing fire						
Type of combustion	Open combustion (B11 _{AS})						
Gas	Natural gas G20, G25 and G25.3 or propane G31 (conversion from natural gas						
	to propane v.v. not	possibl	e)				
Flame picture	Yellow log fire	1					
Input rating (H _s)	G25.3: 4.4kW	G25:	4.4kW	G20: 4.8kW	G31:	4.9kW	
Max output	3.0kW		3.0kW	3.3kW		3.1kW	
Output range	1.4 -3.0kW		1.4 -3.0kW	1.6 -3.3k\	~	1.4 -3.1kW	
Gas usage high	480 l/h		480 l/h	457 l/h		178 l/h	
Gas usage low	228 l/h		228 l/h	219 l/h		80 l/h	
Flue gas flow rate	N.A.		4.8gr/sec	4.8gr/sec		5.4gr/sec	
Flue gas temperature			214°C	223°C		225°C	
CO2-max			3.1%	3.40%		3.10%	
Min. draught required			5Pa	5Pa		5Pa	
Efficiency class	2		D		1		
Energy label	D		D	С		D	
CE-ID (PIN)	0063CM3919						
Sizes	HxWxD = 445x624x330mm (height excluding flue spigot)						
Flue spigot	Ø80mm, top side						
Removal of	Via existing chimney. Natural draught.						
combustion products							
Flueing possibilities	Not applicable						
with wall terminal	N						
Removal of heat	Natural convection						
Control	Mertik GV60-system.						
	Either manual or thermostatic modulating control, by means of temperature					perature	
	sensor on RC control, (adjustable on hand held set). Remote includes clock function with day program (on/off twice a day) and automatic night set back.						
Operation	Radiographic remot		ol 422MUz b	attory approted (ondor 1v	0\/ rossiver	
Operation	4x battery AA)	e conti	UI 433IVITZ, D	allery operated (s	sender ix	ev, receiver	
Ignition		n nilot	hurnor				
Ignition Electrical connection	Electronic ignition on pilot burner						
		No 230VAC connection needed					
Gas connection	Flexible SST gas hose Ø12, L=50cm						
Safety Accessories and	Second thermocouple checks ignition and cross lighting of main burner Mains adapter 230VAC to 6VDC						
	iviairis auaptei 230V	AC 10	UVDC				
options	Engines EEka						
Weight	Engine: 55kg	ubo Ø1	20 I _E00	mo colour oo can	lianca	and logs	
Including	Decorative mantle tube Ø130 L=500, same colour as appliance, wood logs birch, glowing wool, remote control, batteries, Allen key M5 (removal of glass						
	window).						
Special features	Vario burner						
opeciai ieatures	vallo bulllel						

Modification review

Widdill Calloll 16VI	.cw		
Date	Nature of modification		
20-06-2013	New specification		
05-03-2014	G25.3 added. Format modified.		